



NOTES:

- 1) ASSEMBLY PRESSURE TESTED TO 150 PSI.
- 2) MAX OPERATING PRESSURE 100 PSI.

7	MN6	3/8"-16 NUT	STAINLESS STEEL	16
6	33622	3/8" LOCK WASHER	STAINLESS STEEL	16
5	110120346	3/8"-16 x 1 1/2" LONG BOLT	STAINLESS STEEL	16
4	5204LNG	API LOAD ONLY ADAPTER	ALUMINUM	1
3	TETF4ALFP50	4" TTMA FLANGE EXTENSION WITH 1/2" FNPT PORT	ALUMINUM	1
2	400GTTFBL	4" TTMA FLANGE GASKET	BAYLAST™	2
1	3040DLTAL	3" DIXON COUPLER x 4" TTMA FLANGED END	ALUMINUM	1
ITEM NO.	PART NUMBER	DESCRIPTION	MATERIAL	QTY.



The Right Connection™

dixonvalve.com

PROPRIETARY AND CONFIDENTIAL

This drawing is owned by Dixon Valve & Coupling Co. and shall be returned upon demand. It is loaned on condition that it shall not be copied or reproduced or submitted to others without the owners consent. In accepting it subject to this condition the recipient further agrees that this drawing or any design detail or concept disclosed herein shall not be used in any way detrimental to or in competition with the owner. If the recipient does not agree to the terms of this agreement they shall return this drawing immediately. The information contained in this drawing is subject to change without notice.

DO NOT SCALE THIS DRAWING

DIXON U.S.A.

THE RIGHT CONNECTION™

TITLE:

RAIL CAR UNLOADING ASSEMBLY

MATERIAL:

SEE BOM

PART NUMBER:

CG300002N00LNG