Brass Mini Ball Valves

New

The Right Connection®

Application
- Water, oil or gas in commercial, and light industrial applications

Size
- 1/8" to 1/4"

Features
- Blow-out proof stem
- Large raised wrench flat
- Reversible handle
- Full port
- Ideal use for as a gas or gauge cock
- Threads: NPT

Materials
- Forged brass
- Seal: standard FKM
- Seat: TFE

Specifications
- PSI ratings: **600 PSI at 100°F (37°C)**
- Temperature rating: **-40°F to 300°F (-40°C to 148°C)**
- End configurations: female x female and male x female

Approvals
- ANSI Z21.15-2009/CSA 9.1-2009 (**1/2 PSI**)-manually operated gas valves for appliances
- ASME B1644-2002- manually operated metallic gas valves for use in above ground piping systems (**2 and 5 PSIG**)
- MSS SP-100 compliant
- CSA **1/2 PSI** and **5 PSI** gas listings

Size	Part #
1/4"	MBBV25
1/8"	MBBV12
1/4"	MBBMV25
1/8"	MBBMV12

MBBMV25

MBBV25

Dixon Group Canada Limited

2200 Logan Avenue
Winnipeg, MB R2R 0J2
ph: 877.963.4966
email: isales@dixonvalve.ca
canada.dixonvalve.com

© 2022 DVCC • BMBV422