Super Swivels®

The Right Connection®

Applications

- Hose reels, log loaders, automatic car washes, wrecker trucks, horizontal directional drilling, robotics, power line equipment, railroad equipment, mining, and machine tool indexers

Size

- 1/8" to 2-1/2"

Features

- Inline and 90° single plane live swivels, other options include dual plane and extra heavy duty
- Compact design fits in tight areas
- Reduces risk of hose twisting and kinking
- Provides minimal friction allowing free movement of hoses and piping
- Connect directly to hose lines without adapters
- Interchangeable with Parker (PS), Aeroquip, and Hydraulics Inc.
- Rebuild kits available

Materials

- Zinc plated carbon steel
- Other material options upon request:
  - Nickel plated carbon steel
  - 304 and 440c stainless steel (pipe thread only)
- Seal: standard FKM
- Other seal options: nitrile rubber, EPR, neoprene

Specifications

- Pressure range: **3,000 to 10,000 PSI**
- Temperature rating: **-15°F to 250°F (-26°C to 121°C)**

NOTE: Consult Dixon® for additional configurations.

Dixon Group Canada Limited

2200 Logan Avenue
Winnipeg, MB R2R 0J2
ph: 877.963.4966
email: isales@dixonvalve.ca
canada.dixonvalve.comcom

© 2022 DVCC • SS522