

# Dixon<sup>®</sup> Fuel Delivery and Vapor Recovery Elbows



## **Application:**

· delivery of motor fuels to service station underground tanks

#### Size:

· compatible with 4" top seal fill adapters

### Features:

- · famous Bayco heavy duty construction
- available in standard or tall heights to accommodate deep fill boxes
- grease nipple enables greasing of the lever stem
- acetal bushings ensure smooth movement even in the harshest of conditions
- · bolt on inlets allow the inlet to be changed without galling of the threaded inlets
- ball handle lever enables the operator to easily and positively engage the solid bronze locking arms onto the underground adapter
- biofuel compatible up to E100 (100% Ethanol) and B20 (20% Bio Diesel)

See page 2 for part numbers and descriptions.

| Part Number | Description  |
|-------------|--|
| 6200        | standard height elbow only, without inlet connection                               |
| 6200C       | standard height elbow with 3" adapter inlet  |
| 6200A       | standard height elbow with 4" adapter inlet  |
| 6200B       | standard height elbow with 3" coupler inlet  |
| 6200D       | standard height elbow with 4" coupler inlet  |
| 6200T       | elbow with anti-spill sleeve without inlet connection                              |
| 6200AT      | elbow with 4" adapter inlet and anti-spill sleeve                                  |
| 6200X       | tall height elbow only, without inlet connection                                   |
| 6200XC      | tall height elbow with 3" adapter inlet  |
| 6200XA      | tall height elbow with 4" adapter inlet  |
| 6200XB      | tall height elbow with 3" coupler inlet  |
| 6200XD      | tall height elbow with 4" coupler inlet  |
| 6200XT      | tall elbow with anti-spill sleeve without inlet connection                         |
| 6200XAT     | tall elbow with 4" adapter inlet and anti-spill sleeve                             |
| 6500        | standard height full feature elbow only, without inlet connection                  |
| 6500C       | standard height full feature elbow with 3" adapter inlet                           |
| 6500A       | standard height full feature elbow with 4" adapter inlet                           |
| 6500B       | standard height full feature elbow with 3" coupler inlet                           |
| 6500D       | standard height full feature elbow with 4" coupler inlet                           |
| 6500T       | elbow with locking handle and anti-spill sleeve without inlet connection           |
| 6500AT      | elbow with locking handle, 4" adapter inlet and anti-spill sleeve                  |
| 6500X       | tall height full feature elbow only, without inlet connection                      |
| 6500XC      | tall height full feature elbow with 3" adapter inlet                               |
| 6500XA      | tall height full feature elbow with 4" adapter inlet                               |
| 6500XB      | tall height full feature elbow with 3" coupler inlet                               |
| 6500XD      | tall height full feature elbow with 4" coupler inlet                               |
| 6500XT      | tall height full feat. elbow with locking handle, no inlet, with anti-spill sleeve |
| 6500XAT     | tall elbow with locking handle, 4" adapter inlet and anti-spill sleeve             |
| 6530C       | 3" tight fill elbow with 3" inlet adapter  |
| 6530A       | 3" tight fill elbow with 4" inlet adapter  |
| 6000AS      | side seal elbow without inlet connection   |
|             |  |
| 6000ASC     | side seal elbow with 3" adapter inlet  |
| 6000ASA     | side seal elbow with 4" adapter inlet  |
| 6000ASB     | side seal elbow with 3" coupler inlet  |
| 6000ASD     | side seal elbow with 4" coupler inlet  |
| 6000AST     | side seal elbow without inlet connection, with anti-spill sleeve                   |
| 6000ASAT    | side seal elbow with 4" adapter inlet, with anti-spill sleeve                      |
| 6000ASAL    | side seal elbow with 4" adapter inlet, with locking ring                           |
| 6000ASR     | optional add on locking ring. prevents levers from moving                          |
| 6430        | standard height elbow with 3" adapter fuel inlet, 3" adapter vapor outlet          |
| 6430F       | standard height elbow with 3" coupler fuel inlet, 3" adapter vapor outlet          |
| 6400        | standard height elbow with 4" adapter fuel inlet, 3" adapter vapor outlet          |
| 6400F       | standard height elbow with 4" coupler fuel inlet, 3" adapter vapor outlet          |
| 6400FNPT    | standard height elbow with 4" coupler fuel inlet, 3" male npt vapor outlet         |
| 6430X       | tall height elbow with 3" adapter fuel inlet, 3" adapter vapor outlet              |
| 6430XF      | tall height elbow with 3" coupler fuel inlet, 3" adapter vapor outlet              |
| 6400X       | tall height elbow with 4" adapter fuel inlet, 3" adapter vapor outlet              |
| 6400XF      | tall height elbow with 4" coupler fuel inlet, 3" adapter vapor outlet              |
| 6400XFNPT   | tall height elbow with 4" coupler fuel inlet, 3" male npt vapor outlet             |

# **Dixon Group Canada Ltd.**

2200 Logan Avenue • Winnipeg • MB R2R 0J2 email: isales@dixonalve.ca • ph: 877-963-4966 canada.dixonvalve.com

