

Dixon® Cam & Groove Type C Coupler x Hose Shank

Features:

- finger rings are not supplied on 1" Dixon® couplings
- couplers are supplied standard with a Buna-N gasket, other gasket types are available on pages 163 - 166
- ½" Dixon® coupler has only one cam arm
- use Dixon® replacement handles only


Hose ID	356T6 Aluminum Part #	Brass Part #	316 Stainless Steel Part #	Unplated Ductile Iron Part #
1"	100-C-AL	100-C-BR	100-C-SS	---
1½"	150-C-AL	150-C-BR	150-C-SS	150-C-MI
2"	200-C-AL	200-C-BR	200-C-SS	200-C-MI
3"	300-C-AL	300-C-BR	300-C-SS	300-C-MI ¹
4"	400-C-AL	400-C-BR	400-C-SS	400-C-MI ¹
6"	600-C-AL	600-C-BR	600-C-SS	600-C-MI ¹

¹ ductile iron

Only use the crimp style shanks with the crimp style sleeves and ferrules.
Due to differences in dimensions and tolerances for safety reasons, do not interchange other manufacturer's products with Dixon® products.



356T6 aluminum



brass



316 stainless steel



unplated ductile iron

EZ Boss-Lock™ Cam & Groove Type C Coupler x Hose Shank

Feature:

- couplers are supplied standard with a Buna-N gasket, other gasket types are available on pages 163 - 166

Size	316 Stainless Steel Part #
1"	RC100EZCR
1¼"	RC125EZCR
1½"	RC150EZCR
2"	RC200EZCR
3"	RC300EZCR
4"	RC400EZCR
6"	RC600EZCR



Under no circumstances should the EZ Boss-Lock™ cam arms be used on any fitting not specifically designed for their use. See page 122 for further specifications.

