

King™ Hose Menders

- not for compressible products such as air, nitrogen or steam
- The working pressure may vary with the construction of the hose, the type of clamping system used and the application. Consult Dixon® for recommendations.
- In accordance with the ARPM bulletin for oil suction and discharge hose, a coupled length of hose in any size, should be tested to 1½ times the working pressure and held for fifteen minutes without leaking or coupling movement. For additional information and detailed instruction on testing procedures, see the Association for Rubber Products Manufacturer's (ARPM) handbook or visit ARPMINC.com.



for one clamp



Size	Steel Part #
1/4"	KM21
5/16"	KM251
1/2"	KM41
5/8"	KM51
3/4"	KM61
1"	KM81
1-1/4"	KM101
1-1/2"	KM121

for two clamps



Size	Steel Part #
1/2"	KM42
5/8"	KM52
3/4"	KM62
1"	KM82
1¼"	KM102
1½"	KM122
2"	KM162

Barbed Hose Menders



Hose ID	Lead Free Brass ¹	Brass
	Part #	Part #
1/8"	---	BM1
3/16"	---	BM15
1/4" x 1/8"	---	BM2-1
1/4"	1780404CLF	BM2
5/16"	---	BM25
3/8" x 1/4"	---	BM3-2
3/8"	1780606CLF	BM3
1/2" x 3/8"	---	BM4-3
1/2"	1780808CLF	BM4
5/8" x 3/8"	---	BM5-3
5/8" x 1/2"	---	BM5-4
5/8"	---	BM5
3/4" x 1/2"	---	BM6-4
3/4"	---	BM6
1"	---	BM8

¹ Lead free brass <=0.25% lead; Alloy CA2745; Alloy C46400

Short Shank Menders



Size	Length	Previous Part #	316 Stainless Steel Part #
¼"	2-1/32"	1780404SS	RM2
⅜"	2-1/16"	1780606SS	RM3
½"	2-1/16"	1780808SS	RM4
¾"	2-1/2"	1781212SS	RM6