TriFlow Fog Nozzles

Features:
- corrosion resistant plated aluminum
- combination 170° fog and straight stream
- Venturi flow improves straight stream and gallonage
- no nozzle teeth eliminates fingers and voids in the spray pattern thus producing a dense fog

Size	Thread	GPM @ 100 PSI Straight Stream	*6061 T-6 Aluminum* Part #
1½"	NST	**60-100-140**	***TFN150NST-140***
	NPSH	**60-100-140**	***TFN150-140***
1½"	NST	**75-150-200**	***TFN150NST-200***
	NPSH	**75-150-200**	***TFN150-200***

Econo Fog Nozzles

Features:
- rugged, lightweight, corrosion resistant
- supplied without bumper
- for cabinet use, discourages theft
- for use up to 100 PSI (water only)

Size	Thread	Straight Stream @ 100 PSI	*6061-T6 Aluminum* Part #
1"	NPSH	56	***AFN100***
1"	NST	56	***AFN100NST***
1½"	NPSH	56	***AFN150***
1½"	NST	56	***AFN150NST***

Heavy Duty Constant Flow Fog Nozzles

Size	Thread	Length	GPM @ 100 PSI	*Fiberglass Reinforced Composite* Part #
1½"	NPSH	5"	**95**	***CFFR150***
	NST (NH)	5"	**95**	***CFFR150NST***

Garden Hose Nozzles

GHN75

GHN75-B

Features:
- offers two straight streams and one fog pattern [1]
- massive bumper specially formulated to resist damage and aging
- corrosion resistant hard coat

Size	Thread	GPM @ 40 PSI Straight Stream 1st	2nd	*6061-T6 Aluminum* Part #
¾"	GHT - without bumper	**1-2**	**3-4**	***GHN75***
	GHT - with bumper	**1-2**	**3-4**	***GHN75-B***

[1] fog pattern is **4-5 GPM @ 40 PSI**