

Double Clapper Siamese Connections



Features:

- double drop clapper with (2) pin lug swivel inlets provides required 500 GPM minimum to supplement the fire protection as an auxiliary inlet connection to the water supply (250 GPM minimum per inlet)
- exposed Fire Department Connections (FDC) provide an economical method of satisfying local fire codes
- maximum operating pressure: **175 PSI at 70°F (21°C)**
- finish: -P polished or -C polished chrome plated
- UL listed and FM approved


back outlet

Outlet Female NPT Thread	(2) Inlets Female Thread	Branding	Cast Brass Part #
4"	2½" NST(NH)	AutoSprinkler	<b>DCS4025F</b>
		AutoSprinkler	<b>DCS4025F-P</b>
		AutoSprinkler	<b>DCS4025F-C</b>
		StandPipe	<b>DCS4025F-SP</b>
	No Branding	<b>DCS4025F-NB</b>	
6"	3" NST(NH)	AutoSprinkler	<b>DCS4030F</b>
	2½" NST(NH)	AutoSprinkler	<b>DCS6025F</b>
		StandPipe	<b>DCS6025F-SP</b>



Dimensions

Size	A	B
4" x 2½" x 2½"	9⅝"	12¼"
6" x 2½" x 2½"	10¼"	11¾"
4" x 3" x 3"	10"	12½"
6" x 3" x 3"	10⅝"	12½"




bottom outlet

Outlet Female NPT Thread	(2) Inlets Female Thread	Branding	Cast Brass Part #
4"	2½" NST(NH)	AutoSprinkler	<b>90DCS4025F</b>
		AutoSprinkler	<b>90DCS4025F-P</b>
		AutoSprinkler	<b>90DCS4025F-C</b>
		StandPipe	<b>90DCS4025F-SP</b>
	No Branding	<b>90DCS4025F-NB</b>	
6"	3" NST(NH)	AutoSprinkler	<b>90DCS4030F</b>
	2½" NST(NH)	AutoSprinkler	<b>90DCS6025F</b>
		StandPipe	<b>90DCS6025F-SP</b>



Dimensions

Size	A	B	C
4" x 2½" x 2½"	11¾"	9⅝"	7¼"
6" x 2½" x 2½"	11¾"	10¾"	7¼"
4" x 3" x 3"	12½"	10⅝"	7½"
6" x 3" x 3"	12¼"	10⅝"	7¼"



- special threads, branding and finishes are available, consult Dixon® for information
- replacement swivels can be ordered on page 788