

### ¼ Turn Ball Type Wye Valve

**Features:**

- rocker lug swivel
- operates easily under high pressure
- handles are not field replaceable
- seals on the ball are field adjustable and field replaceable
- maximum operating pressure: **175 PSI** (water only) at **70°F (21°C)**

**Specification:**

- meets NSN specifications # 4210-00-255-0234

Inlet Female	(2) Outlets Male	Cast Brass Part #
2½" NST (NH)	1½" NPSH	<b>S7337S</b>



### Full Flow ¼ Turn Ball Type Wye Valves

**Features:**

- recommended for charged pre-connected hose lines
- pin lug swivel
- maximum operating pressure: **175 PSI** (water only) at **70°F (21°C)**
- other configurations are available, contact Dixon® for additional information

Inlet Female Swivel	(2) Outlets Male	Cast Brass Part #
1½" NPSH	1½" NPSH	<b>S7100-15S</b>
1½" NST (NH)	1½" NST (NH)	<b>S7100-15</b>
2½" NST (NH)	1½" NST (NH)	<b>S7100</b>



### Leader Line ¼ Turn Ball Type Wye Valve

**Features:**


- body painted red with chrome trim
- maximum operating pressure: **400 PSI** (water only) at **70°F (21°C)**

Inlet Female NST (NH)	(2) Outlets Male NST (NH)	Brass Part #
2½"	1½"	<b>LLBV2515F</b>



### ¼ Turn Plug Type Wye Valves

**Features:**

- pin lug swivel
- maximum operating pressure: **175 PSI** (water only) at **70°F (21°C)**
- not recommended for charged pre-connected hose 

Inlet Female NST (NH)	(2) Outlets Male	Cast Brass Part #
2½"	1½" NST (NH)	<b>S6175</b>
2½"	1½" NPSH	<b>S6175S</b>

