

## Water-Steam Washdown Station

**Application:**

- fail-safe mixing station safely blends steam and cold water for hot water on demand, should cold water fail, the steam is instantly shut-off

**Features:**

- globe style control valves
- dial thermometer
- in-line check valves
- 3/4" inlet and outlet
- stainless steel hose rack
- mounting plate and hardware for wall mounting
- maximum operating pressure: **150 PSI**
- maximum temperature: **200°F (93°C)**



station is not supplied with hose and nozzle

Bronze  
Part #

**SWDS**

**Pressure Requirements**

| Steam Pressure           |                          | Water Pressure           |                          |
|--------------------------|--------------------------|--------------------------|--------------------------|
| Minimum<br><b>80 PSI</b> | Maximum<br><b>90 PSI</b> | Minimum<br><b>50 PSI</b> | Maximum<br><b>80 PSI</b> |

## Hot and Cold Water Mixing Station

**Features:**

- globe style control valves
- in-line check valves
- 3/4" inlet and outlet
- stainless steel hose rack
- mounting plate and hardware for wall mounting
- maximum operating pressure: **150 PSI**
- maximum temperature: **200°F (93°C)**



station is not supplied with hose and nozzle

Bronze  
Part #

**WDS1**

## Rack for Mixing Station

**Features:**

- stainless steel lag screws
- solid brass mounting crowns
- supplied with mounting hardware
- rack fits SWDS and WDS1 mixing stations
- holds 50' of 3/4" heavy duty industrial grade hose



Stainless Steel  
Part #

**WDSR**