

Turbo Nozzles

Features:

- 15° spray angle
- maximum temperature: **195°F (91°C)**
- ceramic orifice

Nozzle Size	Description	Orifice	Maximum Working PSI	Part #
4.0	¼" female inlet, dk. green	1.30 mm	3,625	AL-TPR25-30
5.5 - 6.0	¼" female inlet, purple	1.50 mm	3,625	AL-TPR25-50
7.0 - 7.5	¼" female inlet, grey	1.70 mm	3,625	AL-TPR25-70
4.0	¼" female inlet, dk. green	1.30 mm	5,075	AL-TPR35-30
5.5	¼" female inlet, purple	1.50 mm	5,075	AL-TPR35-50
6.5	¼" female inlet, grey	1.70 mm	5,075	AL-TPR35-70



Nozzle Holders

Feature:

- maximum temperature: **300°F (149°C)**

Description	Flow (GPM)	Working PSI	Part #
adjustable hi/low nozzle holder with nozzle protector, ¼" female inlet and outlet	7.8	3,650	AL414
change over nozzle, ¼" female inlet, 2 each ¼" female outlets	8	2,900	AL416



AL414



AL416

Inlet Filter for Turbo Nozzles

Features:

- ¼" female inlet, ¼" male outlet
- maximum temperature: **212°F (100°C)**
- 100 mesh filter

Description	Flow (GPM)	Working PSI	Part #
stainless steel, inlet water filter	8	5,000	AR3500



Balance Release Valve

Features:

- working PSI: **4,000 PSI**
- maximum temperature: **195°F (90.6°)**
- GPM: **6.6**
- inlet/outlet: ⅜" female NPT
- bypass: ⅜" female NPT

<i>Brass</i>
Part #
AL702



Water Broom

Features:

- working PSI: **4,000 PSI**
- ¼" quick connect plug

Description	Length	Stainless Steel Part #
4 nozzle broom	16"	AR-BROOM16

