EZ Boss-Lock Type C Couplers

female coupler x hose shank

Feature:

 Couplers are supplied standard with a Buna-N gasket. Other gasket materials are available on pages 58-60.

Size	356T6 Aluminum Part #	<i>Brass</i> Part #	316 Stainless Steel Part #
3⁄4" X 1⁄2"			RC050EZ
3/4"	AC075EZ	BC075EZ	RC075EZ
1"	AC100EZ	BC100EZ	RC100EZCR
11/4"		BC125EZ	RC125EZCR
1½"	AC150EZ	BC150EZ	RC150EZNO
2"	AC200EZ	BC200EZ	RC200EZNO
2½"	AC250EZ		
3"	AC300EZ	BC300EZ	RC300EZCR
4"	AC400EZ	BC400EZ	RC400EZCR
6"	AC600EZ		RC600EZCR
8"	AC800EZ 1		



A

 1 Dixon and Boss-Lock cam and groove couplings do not interchange in the 8" and $\ensuremath{\mathcal{V}}_2$ " sizes.

The 8" Andrew design has 4 cam arms, Boss-Lock design has 2 cam arms.

Under no circumstances should the EZ Boss-Lock cam arms be used on any fitting not specifically designed for their use.

See pages 22 and 56 for further specifications.

Dixon Type D Couplers

female coupler x female NPT

Features:

- Finger rings are not supplied on ½" 1" Dixon couplings.
- ½" Dixon coupler has only one cam arm.
- Couplers are supplied standard with a Buna-N gasket. Other gasket materials are available on pages 58-60.

Size	356T6 Aluminum Part #	Aluminum Hard Coat Part #	<i>Brass</i> Part #	Unplated Iron Part #	316 Stainless Steel Part #
1/2"	50-D-AL		50-D-BR		50-D-SS
3/4"	75-D-AL		75-D-BR		75-D-SS
1"	100-D-AL		100-D-BR		100-D-SS
11/4"	125-D-AL		125-D-BR		125-D-SS
1½"	150-D-AL	150-D-ALH	150-D-BR	150-D-MI	150-D-SS
2"	200-D-AL	200-D-ALH	200-D-BR	200-D-MI	200-D-SS
21/2"	250-D-AL		250-D-BR		250-D-SS
3"	300-D-AL	300-D-ALH	300-D-BR	300-D-MI	300-D-SS
4"	400-D-AL	400-D-ALH	400-D-BR	400-D-MI	400-D-SS
5"	500-D-AL		500-D-BR	500-D-MI	500-D-SS
6"	600-D-AL	600-D-ALH	600-D-BR		600-D-SS
8"	800-D-AL ¹				
8"	801-D-AL				





Dixon and Boss-Lock cam and groove couplings do not interchange in the 8" and ½" sizes.

The 8" Andrew design has 4 cam arms, Boss-Lock design has 2 cam arms.