

Straight Globe Valves

18-217

Features:

- ideal for wet and combination systems
- used with a fire hose rack assembly, or as a fire department outlet connection
- material: cast brass with an aluminum handwheel
- for use up to **300 PSI** at 70°F (21°C)

Inlet Female	Outlet Male	Cast Brass Part #	Powhatan Part #	Wt. Lbs.
1½" NPT	1½" NH (NST)	SGV150F	18-217-00010	6.0
1½" CT	1½" CT	SGV150 ¹	---	6.0
2½" NPT	2½" NH (NST)	SGV250F	18-217-00083	9.6
2½" CT	2½" CT	SGV250 ¹	---	9.6

¹ Customer Thread (*must specify*) refer to legend on page 705.




female NPT x male NH

Inlet Female NPT	Outlet Female NPT	Cast Brass Part #	Powhatan Part #	Wt. Lbs.
1½"	1½"	SGVF150	18-217-00104	6.0
2½"	2½"	SGVF250	18-217-00082	8.0

Dimensions

Size	A	B	C (closed)	D (open)	Wt. Lbs.
1½"	2-3/8"	4-3/4"	7-1/4"	8"	5.0
2½"	3-9/32"	6-9/16"	7-3/8"	8-1/8"	9.3



Wharf Hydrants

18-251

Features:

- used to provide a fire department outlet connection
- pentagon nut at top of spindle discourages unauthorized use
- material: *cast brass*
- hydrostatically tested
- for use up to **300 PSI** at 70°F (21°C)

Inlet Female NPT	Outlet Male NH (NST)	Height Open	Height Closed	Cast Brass Part #	Powhatan Part #	Wt. Lbs.
3"	2½"	16.38	14.25	WHYD3025F	18-251-00008	31
4"	2½"	16.38	14.25	WHYD4025F	18-251-00015	23
4"	4½"	18.13	15.63	WHYD4045F	18-251-00017	41



Replacement Parts

Description	Part #
hand wheel	46-030-00025
pentagon hex nut	44-251-00006