


## ¼ Turn Plug Type Wye Valves

06-175

**Features:**

- pin lug swivel
- for use up to **175 PSI** (water only) at 70°F (21°C)



**⚠** Not recommended for charged pre-connected hose

Inlet Female NH (NST)	(2) Outlets Male	Cast Brass Part #	Powhatan Part #	Wt. Lbs.
2½"	1½" NH (NST)	<b>S6175</b>	06-175-00212	9.0
2½"	1½" NPSH	<b>S6175S</b>	06-175-00223	9.0

**Replacement Part**

Description	Part #	Wt. Lbs.
handle	<b>S6175-H</b>	.35

## ¼ Turn Ball Type Wye Valves

07-337

**Features:**

- rocker lug swivel
- operates easily under high pressure
- handles not field replaceable
- for use up to **175 PSI** (water only) at 70°F (21°C)
- meets NSN specifications # 4210-00-255-0234



Inlet Female	(2) Outlets Male	Cast Brass Part #	Powhatan Part #	Wt. Lbs.
2½" NH (NST)	1½" NPSH	<b>S7337S</b>	07-337-00196	12
2½" CT	1½" NPSH	<b>S7337__S<sup>1</sup></b>	---	12

<sup>1</sup> Customer Thread (*must specify*) refer to legend on page 705

## Full Flow ¼ Turn Ball Type Wye Valves

07-100

**Features:**

- recommended for charged pre-connected hose lines
- pin lug swivel
- for use up to **175 PSI** (water only) at 70°F (21°C)



Female Swivel	(2) Male	Cast Brass Part #	Wt. Lbs.
1½" NPSH	1½" NPSH	<b>S7100-15S</b>	10
1½" NST	1½" NST	<b>S7100-15</b>	10
2½" NST	1½" NST	<b>S7100</b>	11
2½" CT	1½" NPSH	<b>S7100__S<sup>1</sup></b>	11

<sup>1</sup> Customer Thread (*must specify*) refer to legend on page 705, not available with WCT thread.

## Leader Line ¼ Turn Ball Type Wye Valve

**Features:**

- body painted red with chrome trim
- material: *brass*
- for use up to **400 PSI** (water only) at 70°F (21°C)



Female NH (NST)	(2) Male NH (NST)	Brass Part #	Wt. Lbs.
2½"	1½"	<b>LLBV2515F</b>	6.0