

Dixon Northline 2-Way Ball Valves

Application:

This valve will feed two smaller attack lines from one large diameter supply line. The 2½" outlet is a gated ball valve resulting in a safe controlled flow of water.

Features:

The compact 2-way ball valve comes complete with a carrying handle and is available with a Storz or threaded combinations.

- it can be used to distribute water in the opposite direction
- up to **280 PSI** working pressure without relief valve at 70°F (21°C)
- water way: inlet side - 4½" maximum, 2 outlets - 2½" maximum
- material: *high strength aluminum alloy, 356-T6*
- finish hardcoat anodized throughout - minimum thickness 0.001"

Storz Inlet with (2) Outlets



Inlet Storz	Outlet Male	Alum. alloy, 356-T6 Part #	Length	Width	Height	Wt. Lbs.
2½"	2½"	MSBV2525 ¹	9.0"	8.0"	7.0"	6.5
3"	2½"	MSBV325 ¹	9.0"	8.50"	7.0"	6.0
4"	2½"	MSBV425 ¹	12.0"	9.75"	9.0"	13.0
5"	2½"	MSBV525 ¹	12.5"	9.75"	9.0"	15.0
6"	2½"	MSBV625 ¹	12.5"	10.25"	9.0"	15.5



Inlet Storz	(2) Outlet Storz	Alum. alloy, 356-T6 Part #	Length	Width	Height	Wt. Lbs.
2½"	2½"	SBV2525	9.0"	8.00"	7.0"	5.5
3"	2½"	SBV325	9.0"	8.50"	7.0"	6.5
4"	2½"	SBV425	12.0"	9.75"	9.0"	14.5
5"	2½"	SBV525	12.5"	12.00"	9.0"	17.0
6"	2½"	SBV625	13.0"	12.00"	9.0"	19.0

Inlet Storz	(2) Outlet Female	Alum. alloy, 356-T6 Part #	Length	Width	Height	Wt. Lbs.
2½"	2½"	FSBV2525 ¹	9.0"	8.0"	7.0"	6.5
3"	2½"	FSBV325 ¹	9.0"	8.5"	7.0"	6.0
4"	2½"	FSBV425 ¹	12.0"	11.5"	9.0"	15.0
5"	2½"	FSBV525 ¹	12.5"	11.5"	9.0"	17.0
6"	2½"	FSBV625 ¹	13.0"	12.0"	9.0"	19.0

¹ Customer Thread (*must specify*) refer to legend on page 705

Note: all measurements include handles

Female Swivel Inlet with (2) Male Outlets



Inlet Size: 2½"

Inlet Female Swivel	(2) Outlet Male	Part #
2½"	1½"	FMBV25 15 ¹
2½"	2½"	FMBV25 25 ¹
3"	2½"	FMBV30 25 ¹
4"	2½"	FMBV40 25 ¹
4½"	2½"	FMBV45 25 ¹
5"	2½"	FMBV50 25 ¹
6"	2½"	FMBV60 25 ¹



Inlet Size: 3" - 6"

¹ Customer Thread (*must specify*) refer to legend on page 705

Note: all measurements include handles

