

Triple Clapper Siamese Connections

Features:

- branding: see below
- finish: -P polished or -C polished chrome plated
- for use up to **175 PSI** at 70°F (21°C)

back outlet


21-205

Outlet Female NPT	(3) Inlets Female NH (NST)	Branding	Cast Brass Part #	Powhatan Part #	Wt. Lbs.
4"	2½"	AutoSprinkler	TCS4025F	21-205-00003	17.0
		StandPipe	TCS4025F-SP	21-205-00001	17.0
		No Branding	TCS4025F-NB	21-205-00004	17.0
6"	2½"	AutoSprinkler	TCS6025F	21-205-00011	23.5
		StandPipe	TCS6025F-SP	21-205-00008	23.5
		No Branding	TCS6025F-NB	21-205-00029	23.5



Dimensions

Size	A	B	C
4 x 2½ x 2½ x 2½	13-3/4"	10-1/2"	5"
6 x 2½ x 2½ x 2½	13-3/4"	10-1/2"	7-1/2"



bottom outlet


21-206

Outlet Female NPT	(3) Inlets Female NH (NST)	Branding	Cast Brass Part #	Powhatan Part #	Wt. Lbs.
4"	2½"	AutoSprinkler	90TCS4025F	21-206-00002	29
		No Branding	90TCS4025F-NB	21-206-00087	29
6"	2½"	AutoSprinkler	90TCS6025F	21-206-00018	25
		StandPipe	90TCS6025F-SP	21-206-00012	25
		No Branding	90TCS6025F-NB	21-206-00014	25



Dimensions

Size	A	B	C
4 x 2½ x 2½ x 2½	14-1/2"	11-1/2"	7-5/8"
6 x 2½ x 2½ x 2½	14-1/2"	11-1/2"	7-5/8"



- Special threads, branding and finishes are available. Consult Dixon for part number, pricing and availability.
- replacement swivels can be ordered on page 846