

UL Clapper Type Snoots - Pin Lug

Features:

- finish: -P polished, -C polished chrome plated
- other sizes and threads are available, consult Dixon for pricing and availability



polished

Outlet Female NPT	Inlet Female NH (NST)	Cast Brass Part #	Wt. Lbs.
3"	2½"	CSCTF25F30T-P	8
3"	2½"	CSCTF25F30T-C	8



polished chrome plated

Outlet Male NPT	Inlet Female NH (NST)	Cast Brass Part #	Wt. Lbs.
3"	2½"	CSCTM25F30T-P	8
3"	2½"	CSCTM25F30T-C	8

Single Male Outlet with Hex (open snoot)

23-272

Application:

Used to connect fire hose to a standpipe or sprinkler system.

Features:

- finish: -P polished, -C polished chrome plated
- Other sizes and threads are available. Consult Dixon for pricing and availability.



Female NPT	Male	Cast Brass Part #	Powhatan Part #	Wt. Lbs.
2½"	2½" NH (NST)	MOC250F-P	23-272-00003	2.25
	2½" NH (NST)	MOC250F-C	23-272-00006	2.25
	2½" CT	MOC250 ¹	---	2.25
3"	2½" NH (NST)	MOC3025F-P	23-272-00023	3.00
	2½" NH (NST)	MOC3025F-C	23-272-00043	3.00
	2½" CT	MOC3025 ¹	---	3.00
	3" NH (NST)	MOC300F-P	23-272-00030	3.20

¹ Customer Thread (*must specify*) refer to legend on page 705