

Aluminum Female x Male Adapters - Long Handle



Style N56

Female Thread	Aluminum Extrusion - Hardcoat Anodized Male Thread					
	2½"	3"	4"	4½"	5"	6"
4"	N56-40_25_	N56-40_30_	N56-40_40_	N56-40_45_	N56-40_50_	N56-40_60_
4½"	N56-45_25_	N56-45_30_	N56-45_40_	N56-45_45_	N56-45_50_	N56-45_60_
5"	N56-50_25_	N56-50_30_	N56-50_40_	N56-50_45_	N56-50_50_	N56-50_60_
6"	N56-60_25_	N56-60_30_	N56-60_40_	N56-60_45_	N56-60_50_	N56-60_60_

___ Regional Thread (*must specify*) refer to legend below

Part numbers are generated using the rule:

"Female size to Male size," i.e. if the desired part has a 3" male NPT x 2.5" female NST, the part number would be N56-25F30T

Thread Legend

Initials	Common Name	Dixon Suffix	Region Normally Used	2-1/2" ODM ¹	2-1/2" TPI ²
AMA & BCT	Alberta Mutual Aid/ British Columbia Thread	B	British Columbia & Alberta	3.00	8
CSA	Canadian Standard Association	C	Ontario	3.125	5
NS1	Nova Scotia 1	NS	Nova Scotia	3.23	5
QST & QMT	Quebec Standard Thread	Q	Quebec	3.031	7
WCT	Western Canada Thread	W	Saskatchewan & Manitoba	3.25	6
GHT	Garden Hose Thread	G	North America	¹ outside diameter of male ² threads per inch	
NPS	National Pipe Straight	S			
NPT	National Pipe Tapered	T			
NST (NH)	National Standard Thread	F	Most of USA		
NYC	New York Corporation	NYC	Newark, NJ		
NYFD	New York Fire Department	NYFD	New York Fire Department		