Fire Fittings

(Open Snoot) Brass Female Swivel Adapters - Pin Lug

23-270

Features:

Double female rigid hexagon to swivel connection. Rigid end thread is always NPT, hose thread is on swivel end.

finish: -P polished, -C polished chrome plated

· Other configurations are also available. Consult Dixon for pricing and availability.

Female Swivel	Female Rigid	Cast Brass	Wt.
Thread	Thread	Part #	Lbs.
11/2" NH (NST)	1½" NPT	SF150F	1.0
11/2" NPSH	1½" NPT	SF150S	1.0
21/2" NH (NST)	1½" NPT	SF25F15T	3.6
21⁄2" CT1	1½" NPT	SF2515T1	3.6
21/2" NH (NST)	2" NPT	SF25F20T	2.8
21⁄2" CT1	2" NPT	SF2520T1	2.8
21⁄2" CT1	21⁄2" CT1	SF25 1	2.8
21⁄2" NH (NST)	21⁄2" NPT	SF250F	2.9
21/2" NH (NST)	21⁄2" NPT	SF250F-P	2.8
21⁄2" NH (NST)	21⁄2" NPT	SF250F-C	2.9
21⁄2" NPSH	21⁄2" NPT	SF250S	2.9
21⁄2" CT1	21⁄2" NPT	SF2525T1	2.9
21/2" NH (NST)	3" NPT	SF25F30T	3.9
21/2" CT1	3" NPT	SF2530T1	3.9
3" NH (NST)	3" NPT	SF300F	4.6
3" NH (NST)	3" NPT	SF300F-P	4.6
3" NH (NST)	3" NPT	SF300F-C	4.6
4" NH (NST)	4" NPT	SF400F	10.0



¹ Customer Thread (*must specify*) refer to legend on page 705

(Open Snoot) Female Swivel Adapters - Rocker Lug

23-270

Feature:

· Other configurations are also available. Consult Dixon for pricing and availability.

Female	Female	Cast Brass	Wt.
Threads	Threads	Part #	Lbs.
11/2" NH (NST)	1½" NPT	RSF150F	1.0
21⁄2" NH (NST)	1½" NPT	RSF25F15T	4.9
21⁄2" CT	1½" NPT	RSF2515T 1	4.9
21⁄2" NH (NST)	2" NPT	RSF25F20T	3.7
21⁄2" CT	2" NPT	RSF2520T 1	3.7
21⁄2" NH (NST)	21⁄2" NPT	RSF250F	3.8
21⁄2" CT	21⁄2" NPT	RSF2525T 1	3.8
21⁄2" CT	2½" CT	RSF2525 1	3.8
21/2" NH (NST)	3" NPT	RSF25F30T	4.7
21⁄2" CT	3" NPT	RSF2530T1	4.7



¹ Customer Thread (must specify) refer to legend on page 705

All adapters are made to approved Dixon specifications. The Powhatan part numbers provided on this page are for quick reference purposes.