

Screw Pitch Gauge

Features:

- used to determine threads per inch
- 30 leaves

<i>Stainless Steel</i> Part #	Powhatan Part #	Wt. Lbs.
TPG	29-425-00001	.35



Long Handle Short Shank Suction Hose Females

Features:

- powder coated aluminum swivel nut
- for suction and low pressure discharge only

Female Swivel NH (NST)	Hose Size	Part #	Wt. Lbs.
4"	4"	LHFS400F	3.0
4½"	4"	LHFS4045F	3.4



Cam and Groove Adapters - Pin Lug

Features:

- pin lugs allow for easy connection using standard spanner and hydrant wrenches
- supplied with buna-N washer in the threaded end
- see pages 792-794 for lug wrenches

Female NH (NST)	Male Adapter	<i>Aluminum</i> Part #	Wt. Lbs.
1½"	1½"	AHA1515ADP	0.5
2½"	2½"	AHA2525ADP	0.6



Female NH (NST)	Male Adapter	<i>Brass</i> Part #	Wt. Lbs.
1½"	1½"	HA1515ADP	0.8
2½"	2½"	HA2525ADP	2.0



Note: Other thread configurations are available by using fire thread adapters with cam & groove connections, please contact Dixon for more information.

NST Threaded Cam and Groove Adapter

Cam and Groove	NST	<i>Aluminum</i> Part #
2"	2½" Male	2025-F-ALNST
2"	4" Male	2040-F-ALNST
2"	2½" Female	2025-D-ALNST
3"	2½" Female	3025-A-ALNST
4"	2½" Female	4025-D-ALNST



Note: Other thread configurations are available by using fire thread adapters with cam & groove connections, please contact Dixon for more information.