

Dixon Northline Storz Fittings



FSA-Storz x Rigid Female

Application:

designed to be used where ever a non-valved, locking coupling is required

Features:

- machined from forged 6061 - T6 aluminum
- Buna-N gaskets
- working pressure: **150 PSI** at 70°F (21°C)
- cast aluminum lock lever assembly on 4", 5" and 6"

Storz Size	Hardcoat Anodized Components per MIL-A-8625 Type III Class 1 Female Rigid Thread									
	1"	1½"	2"	2½"	3"	3½"	4"	4½"	5"	6"
1"	FSA1010_									
1½"	FSA1510_	FSA1515_		FSA1525_						
2"		FSA2015_	FSA2020_	FSA2025_						
2½"		FSA2515_	FSA2520_	FSA2525_	FSA2530_					
3"			FSA3020_	FSA3025_	FSA3030_					
4"				FSA4025_	FSA4030_	FSA4035_	FSA4040_	FSA4045_	FSA4050_	FSA4060_
5"				FSA5025_	FSA5030_	FSA5035_	FSA5040_	FSA5045_	FSA5050_	FSA5060_
6"							FSA6040_	FSA6045_	FSA6050_	FSA6060_

____ Customer Thread (*must specify*) refer to legend on next page