

Dixon Northline Storz Fittings



SFSA - Storz x Swivel Female Adapter - Rocker Lug / Long Handle

Features:

- machined from forged 6061 - T6 aluminum
- Buna-N gaskets
- working pressure: **150 PSI** at 70°F (21°C)
- cast aluminum lock lever assembly on 4", 5" and 6"

Storz Size	Hardcoat Anodized Components per MIL-A-8625 Type III Class 1 Female Swivel Thread						
	2½"	3"	3½"	4"	4½"	5"	6"
2½"	SFSA2525_						
3"	SFSA3025_	SFSA3030_					
4"	SFSA4025_	SFSA4030_	SFSA4035_	SFSA4040_	SFSA4045_	SFSA4050_	SFSA4060_
5"	SFSA5025_	SFSA5030_	SFSA5035_	SFSA5040_	SFSA5045_	SFSA5050_	SFSA5060_
6"				SFSA6040_	SFSA6045_	SFSA6050_	SFSA6060_

___ Customer Thread (*must specify*) refer to legend below

Long Handle - LH suffix

Rocker Lug - furnished standard

Thread Legend

Initials	Common Name	Dixon Suffix	Region Normally Used	2-1/2" ODM ¹	2-1/2" TPI ²
AMA & BCT	Alberta Mutual Aid/ British Columbia Thread	B	British Columbia & Alberta	3.00	8
CSA	Canadian Standard Association	C	Ontario	3.125	5
NS1	Nova Scotia 1	NS	Nova Scotia	3.23	5
QST & QMT	Quebec Standard Thread	Q	Quebec	3.031	7
WCT	Western Canada Thread	W	Saskatchewan & Manitoba	3.25	6
GHT	Garden Hose Thread	G	North America	¹ outside diameter of male ² threads per inch	
NPS	National Pipe Straight	S			
NPT	National Pipe Tapered	T			
NST (NH)	National Standard Thread	F	Most of USA		
NYC	New York Corporation	NYC	Newark, NJ		
NYFD	New York Fire Department	NYFD	New York Fire Department		