

## Dixon Northline Storz Fittings



## SFSA30 - Storz x Female Swivel 30° Elbow - Rocker Lug

**Features:**

- machined from forged 6061 - T6 aluminum
- Buna-N gaskets
- working pressure: **150 PSI** at 70°F (21°C)
- cast aluminum lock lever assembly on 4", 5" and 6"
- screens available for 4" and 5" heads, consult Dixon for pricing

Storz Size	Hardcoat Anodized Components per MIL-A-8625 Type III Class 1 Female Swivel Thread						
	2½"	3"	3½"	4"	4½"	5"	6"
2½"	SFSA30-2525_	SFSA30-2530_					
3"	SFSA30-3025_	SFSA30-3030_					
4"	SFSA30-4025_	SFSA30-4030_	SFSA30-4035_	SFSA30-4040_	SFSA30-4045_	SFSA30-4050_	SFSA30-4060_
5"	SFSA30-5025_	SFSA30-5030_	SFSA30-5035_	SFSA30-5040_	SFSA30-5045_	SFSA30-5050_	SFSA30-5060_
6"				SFSA30-6040_	SFSA30-6045_	SFSA30-6050_	SFSA30-6060_

\_\_\_\_ Customer Thread (*must specify*) refer to legend on page 705

## NCS-CSF - 150 lbs. Carbon Steel Flange x Storz

**Feature:**

- storz: *hardcoated aluminum*
- flange: *carbon steel*

Storz Size	150# Flange Size		
	4"	5"	6"
4"	NCS-CSF-STZ440	NCS-CSF-STZ540	NCS-CSF-STZ640
5"	NCS-CSF-STZ450	NCS-CSF-STZ550	NCS-CSF-STZ650
6"	NCS-CSF-STZ460	NCS-CSF-STZ560	NCS-CSF-STZ660