

Dixon Northline Storz Fittings

Features:

- machined from forged 6061 - T6 aluminum
- hardcoat anodized components per MIL-A-8625 Type III Class 1
- Buna-N gaskets
- working pressure: **150 PSI** at 70°F (21°C)
- cast aluminum lock lever assembly on 4", 5" and 6"

SFSA30 - Storz x Female Swivel 30° Elbow - Long Handle



Storz Size	Hardcoat Anodized Components per MIL-A-8625 Type III Class 1 Female NST Swivel Thread			
	4"	4½"	5"	6"
4"	SFSA30-4040F-LH	SFSA30-4045F-LH	SFSA30-4050F-LH	SFSA30-4060F-LH
5"	SFSA30-5040F-LH	SFSA30-5045F-LH	SFSA30-5050F-LH	SFSA30-5060F-LH
6"	SFSA30-6040F-LH	SFSA30-6045F-LH	SFSA30-6050F-LH	SFSA30-6060F-LH

MSA - Storz x Rigid Male



Storz Size	Male Thread								
	1"	1½"	2"	2½"	3"	4"	4½"	5"	6"
1"		MSA1015_	MSA1020_	MSA1025_					
1½"	MSA1510_	MSA1515_	MSA1520_	MSA1525_					
2"		MSA2015_	MSA2020_	MSA2025_	MSA2030_				
2½"		MSA2515_	MSA2520_	MSA2525_	MSA2530_				
3"			MSA3020_	MSA3025_	MSA3030_				
4"				MSA4025_	MSA4030_	MSA4040_	MSA4045_	MSA4050_	MSA4060_
5"				MSA5025_	MSA5030_	MSA5040_	MSA5045_	MSA5050_	MSA5060_
6"						MSA6040_	MSA6045_	MSA6050_	MSA6060_

___ Customer Thread (*must specify*) refer to legend on page 705