


## Brass Plugs Pin Lug

17-127

**Features:**

- finish: -P polished, -C polished chrome plated
- NOT intended for pressure applications - for debris and thread protection only 

Thread NH (NST)	Cast Brass Part #	Wt. Lbs.
1½"	<b>FP150F</b>	0.73
1½"	<b>FP150F-P</b>	0.73
1½"	<b>FP150F-C</b>	0.73
2½"	<b>FP250F</b>	1.46
2½"	<b>FP250F-P</b>	1.46
2½"	<b>FP250F-C</b>	1.46
3"	<b>FP300F</b>	1.40
3"	<b>FP300F-P</b>	1.40
3"	<b>FP300F-C</b>	1.40
4"	<b>FP400F</b>	4.50
4½"	<b>FP450F</b>	4.90
6"	<b>FP600F</b>	4.90



cast brass



polished brass

Thread NPSH	Cast Brass Part #	Wt. Lbs.
1½"	<b>FP150</b>	0.73
2½"	<b>FP250</b>	1.40
3"	<b>FP300</b>	2.00
4"	<b>FP400</b>	4.20
2½" CT <sup>1</sup>	<b>FP250</b> <sup>1</sup>	1.46



chrome brass

<sup>1</sup> Customer Thread (*must specify*) refer to legend below

## Rocker Lug

17-127

**Features:**

- finish: -P polished, -C polished chrome plated

Thread NH (NST)	Cast Brass Part #	Wt. Lbs.
1½"	<b>RFP150F</b>	0.76
1½"	<b>RFP150F-C</b>	0.76
2½"	<b>RFP250F</b>	1.88
2½"	<b>RFP250F-C</b>	1.88
2½" CT	<b>RFP250</b>	1.88



<sup>1</sup> Customer Thread (*must specify*) refer to legend below

## Thread Legend

Initials	Common Name	Dixon Suffix	Region Normally Used	2-1/2" ODM <sup>1</sup>	2-1/2" TPI <sup>2</sup>
AMA & BCT	Alberta Mutual Aid/ British Columbia Thread	<b>B</b>	British Columbia & Alberta	3.00	8
CSA	Canadian Standard Association	<b>C</b>	Ontario	3.125	5
NS1	Nova Scotia 1	<b>NS</b>	Nova Scotia	3.23	5
QST & QMT	Quebec Standard Thread	<b>Q</b>	Quebec	3.031	7
WCT	Western Canada Thread	<b>W</b>	Saskatchewan & Manitoba	3.25	6
GHT	Garden Hose Thread	<b>G</b>	North America	<sup>1</sup> outside diameter of male <sup>2</sup> threads per inch	
NPS	National Pipe Straight	<b>S</b>			
NPT	National Pipe Tapered	<b>T</b>			
NST (NH)	National Standard Thread	<b>F</b>	Most of USA		
NYC	New York Corporation	<b>NYC</b>	Newark, NJ		
NYFD	New York Fire Department	<b>NYFD</b>	New York Fire Department		