

## Constant Flow Fog Nozzles

**Features:**

- red polycarbonate with bumper and black plastic and steel stem
- provides consistent volume at any spray angle
- adjusts from Straight Stream to Fog
- 1" and 1½" are ULC listed
- for use up to **100 PSI** (water only) at 70°F (21°C)

Size	Thread	90° Spray GPM @ 100 PSI	Polycarbonate Part #	Wt. Lbs.
¾"	GHT	8	<b>CFB75GHT</b>	0.42
1"	SIPT	22	<b>CFB100S</b>	0.38
1½"	SIPT	75	<b>CFB150S</b> <sup>1</sup>	0.44
1½"	SIPT	150	<b>HGCFB150S</b> <sup>2</sup>	0.50
2"	SIPT	75	<b>CFB2015S</b> <sup>1</sup>	0.45
2"	SIPT	150	<b>CFB200S</b> <sup>2</sup>	0.53
1"	NH (NST)	22	<b>CFB100NST</b>	0.37
1½"	NH (NST)	75	<b>CFB150NST</b> <sup>1</sup>	0.44
1½"	NH (NST)	150	<b>HGCFB150NST</b> <sup>2</sup>	0.51
2½"	NH (NST)	150	<b>CFB250NST</b> <sup>3</sup>	2.00
2½"	NH (NST)	215	<b>HGCFB250NST</b> <sup>2</sup>	1.90
1½"	CF	75	<b>CFB150CF</b> <sup>1</sup>	0.43
2½"	CF	150	<b>CFB250CF</b> <sup>3</sup>	2.00
2½"	CT	150	<b>CFB250</b> <sup>4</sup>	2.00



2½" nozzle with handles  
CFB250NST



2½" nozzle without handles  
HGCFB250NST



1½" nozzle

\_\_\_ Customer Thread (*must specify*) refer to legend on page 705

- <sup>1</sup> standard flow
- <sup>2</sup> high flow
- <sup>3</sup> provided with handles
- <sup>4</sup> only available with BAT or NST thread

## Blue Refinery Fog Nozzles

**Features:**

- blue polycarbonate with bumper and black plastic and steel stem
- glass-filled
- provides consistent volume at any spray angle
- adjusts from Straight Stream to Fog
- resistant to petrochemicals
- for use up to **100 PSI** (water only) at 70°F (21°C)

Size	Thread	90° Spray GPM @ 100 PSI	Polycarbonate Part #	Wt. Lbs.
1½"	SIPT	75	<b>RNB150S</b>	0.48
1½"	NH (NST)	75	<b>RNB150NST</b>	0.47



**Features:**

- used on constant flow and refinery fog nozzles

## Gaskets

dimensions are nominal

Size	Thread	ID	OD	Thickness	Buna-N Part #	Wt. Lbs.
1"	SIPT	0.900"	1.270"	0.125"	<b>CFG100S</b>	.003
1½"	SIPT	1.510"	1.878"	0.125"	<b>CFG150S</b>	.005
2"	SIPT	1.680"	2.340"	0.156"	<b>CFG200S</b>	.013
1"	NH (NST)	0.900"	1.270"	0.125"	<b>CFG100NST</b>	.003
1½"	NH (NST)	1.510"	1.906"	0.125"	<b>CFG150NST</b>	.003
2½"	NH (NST)	2.250"	3.000"	0.187"	<b>CFG250NST</b>	.020

