

UL **FM** Domestic Rack Nozzles



Features:

- supplied without bumper
- delivers 30° - 60° - 90° fog pattern - shut-off - straight stream - fog
- for use up to **100 PSI** (water only) at 70°F (21°C)
- U/L listed and Factory Mutual approved for class A and B fires

Size	Thread	90° Spray GPM @ 100 PSI	Brass Part #	Powhatan Part #	Old Part #	Wt. Lbs.
1½"	NH (NST)	80	BRN150NST	02-465-00001		1.4
1½"	NPSH	80	BRN150	02-465-00002	BRN150S	1.4

UL **FM** Global Rack Nozzles



Features:

- supplied without bumper
- delivers 30° - 60° - 90° fog pattern - shut-off - straight stream - fog
- for use up to **100 PSI** (water only) at 70°F (21°C)
- U/L listed and Factory Mutual approved for class A and B fires

Size	Thread	90° Spray GPM @ 100 PSI	Brass Part #	Wt. Lbs.
1½"	NH (NST)	80	BRN150NST-I	1.3

Plain Hose Nozzles

Features:

- finish: satin
- for use up to **100 PSI** (water only) at 70°F (21°C)



Size	Thread	ID	OD	Brass Part #	Wt. Lbs.
¾"	GHT	6"	1/4"	BN6	0.4
¾"	NPSH	6"	1/4"	BN7	0.4
1"	NPSH	8"	5/16"	BN10	0.5
1¼"	NPSH	10"	3/8"	BN12	1.0
1½"	NPSH	10"	1/2"	BN15	1.1
2"	NPSH	12"	9/16"	BN20	2.6
2½"	NPSH	12"	1"	BN25	3.4
1"	NH (NST)	8"	5/16"	BN10F	0.7
1½"	NH (NST)	10"	1/2"	BN15F	1.2
2½"	NH (NST)	12"	1"	BN25F	2.8
2½"	CT	12"	1"	BN25 ¹	3.4

¹ ___ Customer Thread (*must specify*) refer to legend on page 705 (not available in WCT thread)

All nozzles are made to approved Dixon specifications. The Powhatan part numbers provided in this chart are for quick reference purposes.