

Synthetic Mill Hose



Ideal for open end discharge applications. **Not intended for fire fighting service.**

Features:

- outer construction: *single jacket, all synthetic*
- tube construction: *black, natural rubber liner*
- ratings:
 - rated pressure: **250 PSI** at 70°F (21°C)
 - working pressure: **125 PSI** at 70°F (21°C)
 - temperature range: -15°F to 118°F

Uncoupled



Size	Bowl	Length	Part #
1"	1-1/4"	50'	M10-50UC
1"	1-1/4"	100'	M10-100UC
1½"	1-11/16"	25'	M15-25UC
1½"	1-11/16"	50'	M15-50UC
1½"	1-11/16"	100'	M15-100UC
2"	2-1/4"	25'	M20-25UC
2"	2-1/4"	50'	M20-50UC
2"	2-1/4"	100'	M20-100UC
2½"	2-11/16"	25'	M25-25UC
2½"	2-11/16"	50'	M25-50UC
2½"	2-11/16"	100'	M25-100UC
3"	3-3/8"	25'	M30-25UC
3"	3-3/8"	50'	M30-50UC
3"	3-3/8"	100'	M30-100UC
4"	4-3/8"	25'	M40-25UC
4"	4-3/8"	50'	M40-50UC
4"	4-3/8"	100'	M40-100UC
6"	6-3/8"	25'	M60-25UC
6"	6-3/8"	50'	M60-50UC

Consult Dixon for pricing and availability for any of the following features:

- 75' lengths

Coupled



Coupled with female and male expansion ring couplings

Size	Length	Aluminum Rocker Lug NPSH Part #	Aluminum Rocker Lug NST Part #	Aluminum Rocker Lug Customer Thread Part #	Aluminum Rocker Lug MNPT x MNPT Part #
1½"	50'	M15-50RAS	M15-50RAF	---	M15-50RAT
1½"	100'	M15100RAS	M15100RAF	---	M15100RAT
2"	50'	M20-50RAS	---	---	M20-50RAT
2"	100'	M20100RAS	---	---	M20100RAT
2½"	25'	M25-25RAS	M25-25RAF	M25-25RA__	---
2½"	50'	M25-50RAS	M25-50RAF	M25-50RA__	M25-50RAT
2½"	100'	M25100RAS	M25100RAF	M25100RA__	M25100RAT

¹ Customer Thread (*must specify*) refer to legend on page 705

Consult Dixon for pricing and availability for any of the following features:

- 75' lengths
- other threads and configurations