

Synthetic Double Jacket Mill Hose

Application:



- Ideal for open end discharge applications. **Not intended for fire fighting service.**

Features:

- Outer construction: double jacket, all polyester
- Tube construction: black, natural rubber liner
- rated pressure: **250 PSI** at 70°F (21°C)
- working pressure: **200 PSI** at 70°F (21°C)



Uncoupled

Size	Bowl	Length	Part #
1½"	1-13/16"	50'	DM15-50UC
1½"	1-13/16"	100'	DM15-100UC
2"	2-5/16"	50'	DM20-50UC
2"	2-5/16"	100'	DM20-100UC
2½"	2-7/8"	50'	DM25-50UC
2½"	2-7/8"	100'	DM25-100UC

* Double jacket hoses are **not** recommended for use with field reattachable couplings (Flat Seal).

Coupled

NH (NST) Thread

Size	Bowl	Length	Part #
1½"	1-13/16"	50'	DM15-50RAF
1½"	1-13/16"	100'	DM15100RAF
2½"	2-7/8"	50'	DM25-50RAF
2½"	2-7/8"	100'	DM25100RAF

NPSH Thread

Size	Bowl	Length	Part #
1½"	1-13/16"	50'	DM15-50RAS
1½"	1-13/16"	100'	DM15100RAS
2½"	2-7/8"	50'	DM25-50RAS
2½"	2-7/8"	100'	DM25100RAS

Customer Thread

Size	Bowl	Length	Part #
2½"	2-7/8"	50'	DM25-50RA ¹
2½"	2-7/8"	100'	DM25100RA ¹

¹ Customer Thread (*must specify*) refer to legend on page 705

Aluminum MNPT x MNPT

Size	Bowl	Length	Part #
1½"	1-13/16"	50'	DM15-50RAT
1½"	1-13/16"	100'	DM15100RAT
2"	2-5/16"	50'	DM20-50RAT
2"	2-5/16"	100'	DM20100RAT
2½"	2-7/8"	50'	DM25-50RAT
2½"	2-7/8"	100'	DM25100RAT

¹ Customer Thread (*must specify*) refer to legend on page 705

Consult Dixon for pricing and availability for any of the following features:

- 75' lengths
- other threads and configurations

