

300# Single Jacket All-Polyester Fire Hose - White

Features:

- outer construction: single jacket, all polyester
- tube construction: black, extruded EPDM rubber liner
- ratings:
 - proof pressure: **300 PSI** at 70°F (21°C)
 - service test pressure: **150 PSI** at 70°F (21°C)
 - working pressure: **135 PSI** at 70°F (21°C)

Uncoupled

Size	Bowl	Length	Part #
1½"	1-3/4"	50'	A315-50UC
1½"	1-3/4"	100'	A315-100UC
2"	2-1/4"	50'	A320-50UC
2"	2-1/4"	100'	A320-100UC
2½"	2-13/16"	50'	A325-50UC
2½"	2-13/16"	100'	A325-100UC
3"	3-3/8"	50'	A330-50UC
3"	3-3/8"	100'	A330-100UC



Coupled

NH (NST) Thread

Size	Coupling Type	Length	Part #
1½"	rocker lug, aluminum	50'	A315-50RAF
1½"	rocker lug, aluminum	100'	A315100RAF
1½"	rocker lug, brass	50'	A315-50RBF
1½"	rocker lug, brass	100'	A315100RBF
2½"	rocker lug, aluminum	50'	A325-50RAF
2½"	rocker lug, aluminum	100'	A325100RAF
2½"	rocker lug, brass	50'	A325-50RBF
2½"	rocker lug, brass	100'	A325100RBF

NPSH Thread

Size	Coupling Type	Length	Part #
1½"	rocker lug, aluminum	50'	A315-50RAS
1½"	rocker lug, aluminum	100'	A315100RAS
2½"	rocker lug, aluminum	50'	A325-50RAS
2½"	rocker lug, aluminum	100'	A325100RAS
3"	rocker lug, aluminum	50'	A325-50RAS
3"	rocker lug, aluminum	100'	A325100RAS

Customer Thread

Size	Coupling Type	Length	Part #
2½"	rocker lug, aluminum	25'	A325-25RA ¹
2½"	rocker lug, aluminum	50'	A325-50RA ¹
2½"	rocker lug, aluminum	100'	A325100RA ¹

¹ Customer Thread (*must specify*) refer to legend on page 705

Consult Dixon for pricing and availability for any of the following features:

- other threads and configurations



O