

500# Single Jacket All-Polyester Fire Hose - White

Features:

- outer construction: single jacket, all polyester
- tube construction: black, extruded EPDM rubber liner
- ratings:
 - proof pressure: **500 PSI** at 70°F (21°C)
 - service test pressure: **250 PSI** at 70°F (21°C)
 - working pressure: **225 PSI** at 70°F (21°C)

Uncoupled



Size	Bowl	Length	Part #
1"	1¼"	50'	A510-50UC
1"	1¼"	100'	A510-100UC
1½"	1¾"	50'	A515-50UC
1½"	1¾"	100'	A515-100UC
2½"	2-13/16"	50'	A525-50UC
2½"	2-13/16"	100'	A525-100UC

Coupled



Coupled with female and male expansion ring couplings

Size	Length	Rocker Lug Aluminum NST (NH) Part #	Rocker Lug Brass NST (NH) Part #	Rocker Lug Aluminum NPSH Part #	Rocker Lug Aluminum Customer Thread Part #
1"	50'	---	---	A510-50RAS	---
1"	100'	---	---	A510100RAS	---
1½"	25'	A515-25RAF	A515-25RBF	A515-25RAS	---
1½"	50'	A515-50RAF	A515-50RBF	A515-50RAS	---
1½"	100'	A515100RAF	A515100RBF	A515100RAS	---
2½"	25'	A525-25RAF	A525-25RBF	---	A525-25RA__
2½"	50'	A525-50RAF	A525-50RBF	---	A525-50RA__
2½"	100'	A525100RAF	A525100RBF	---	A525100RA__

__ Customer Thread (*must specify*) refer to legend on page 705

Consult Dixon for pricing and availability for any of the following features:

- other threads and configurations