

Brass Expansion Ring Couplings

Features:

- special tooling is required to attach these couplings to hose
- all couplings come complete with expansion rings, swivel and tail washers

Couplings for Rack Hose

Features:

- lugs on female only

Hose Size	Lugs	Thread	Bowl	Brass Part #	Wt. Lbs.
1½"	rocker	NPSH	1-11/16"	RRH15168	1.37
1½"	rocker	NST (NH)	1-11/16"	RRH15168F	1.37
1½"	pin	NPSH	1-11/16"	RH16168	0.55
1½"	pin	NH (NST)	1-11/16"	RH16168F	0.64

Couplings for Single Jacket Hose

Features:

- lugs on female and male

Rocker Lug Couplings

Hose Size	Thread Type	Bowl	Brass Part #	Wt. Lbs.
1½"	NPSH	1-3/4"	RS15175	2.23
1½"	NPSH	1-13/16"	RS15181	2.20
2½"	NPSH	2-13/16"	RS25281	5.50
1½"	NH (NST)	1-3/4"	RS15175F	2.23
1½"	NH (NST)	1-13/16"	RS15181F	2.20
2½"	NH (NST)	2-13/16"	RS25281F	5.50
2½"	NH (NST)	2-7/8"	RS25287F	5.60
2½"	CT	2-13/16"	RS25281 __	5.50
2½"	CT	2-7/8"	RS25287 __	5.60

Pin Lug Couplings

Hose Size	Thread Type	Bowl	Brass Part #	Wt. Lbs.
1½"	NPSH	1-3/4"	S15175	2.38
1½"	NPSH	1-13/16"	S15181	2.12
2½"	NPSH	2-13/16"	S25281	4.43
2½"	NPSH	2-7/8"	S25287	4.50
1½"	NH (NST)	1-3/4"	S15175F	2.12
1½"	NH (NST)	1-13/16"	S15181F	2.09
2½"	NH (NST)	2-13/16"	S25281F	5.65
2½"	NH (NST)	2-7/8"	S25287F	5.76
2½"	CT	2-13/16"	S25281 __	5.65
2½"	CT	2-7/8"	S25287 __	5.76

__ Customer Thread (*must specify*) refer to legend on page 705

Couplings for Double Jacket Hose

Features:

- lugs on female and male

Rocker Lug Couplings

Hose Size	Thread Type	Bowl	Brass Part #	Wt. Lbs.
1½"	NPSH	1-15/16"	RD15193	2.11
1½"	NPSH	2-1/16"	RD15206	2.08
2½"	NPSH	3"	RD253	6.12
1½"	NH (NST)	1-15/16"	RD15193F	2.11
1½"	NH (NST)	2-1/16"	RD15206F	2.08
2½"	NH (NST)	3"	RD253F	6.12
2½"	CT	3"	RD253 __	6.12

Pin Lug Couplings

Hose Size	Thread Type	Bowl	Brass Part #	Wt. Lbs.
1½"	NPSH	1-15/16"	D15193	2.49
2½"	NPSH	3"	D253	5.16
1½"	NH (NST)	1-15/16"	D15193F	2.58
2½"	NH (NST)	3"	D253F	6.00
2½"	CT	3"	D253 __	6.00

__ Customer Thread (*must specify*) refer to legend on page 705



Consult Dixon for pricing and availability for other sizes and threads or male or females only.