

Stainless Steel Ball Valves

Full Port, Locking Handle

Features:

- for use in water, oil and gas
- 1/4" - 2" rated to **1000 PSI** WOG (CWP); **100 PSI** saturated steam
- 316 stainless steel body, ball and stem
- PTFE seat, joint gasket and thrust washer
- plastic cover on handle
- blow-out proof stem design
- full port
- temperature range **0°F to 356°F (-18°C to 180°C)**
- lockable

female NPT x female NPT

Size	Port Type	316 Stainless Steel Part #
1/4"	full	SSLBVG25
3/8"	full	SSLBVG38
1/2"	full	SSLBVG50
3/4"	full	SSLBVG75
1"	full	SSLBVG100
1-1/4"	full	SSLBVG125
1-1/2"	full	SSLBVG150
2"	full	SSLBVG200



Reduced Port, Locking Handle

Features:

- for use in water, oil and gas
- rated to **1000 PSI** WOG; **100 PSI** saturated steam
- 316 stainless steel body, ball and stem
- PTFE seat, joint gasket and thrust washer
- plastic cover on handle
- blow-out proof stem design
- reduced port
- temperature range **-20°F to 450°F (-29°C to 232°C)**
- lockable

Size	Port Type	316 Stainless Steel Part #
1/4"	reduced	SSLBV25SP
3/8"	reduced	SSLBV38SP
1/2"	reduced	SSLBV50SP
3/4"	reduced	SSLBV75SP
1"	reduced	SSLBV100SP
1-1/4"	reduced	SSLBV125SP
1-1/2"	reduced	SSLBV150SP
2"	reduced	SSLBV200SP

