

## Boss Holedall Fittings

### Applications:

Boss Holedall fittings are designed for air and liquid applications where a permanent, low profile clamping system is desired. Both fittings are supplied with carbon steel ferrules. Consult Dixon for swage and/or crimp specifications.



Not for steam service.

D



Size	Hose OD		Plated Iron / Steel	Stainless Steel
	From:	To:	Part #	Part #
¾"	1-10/64"	1-14/64"	<b>GF26P1</b>	---
	1-15/64"	1-18/64"	<b>GF26P2</b>	---
	1-19/64"	1-22/64"	<b>GF26P3</b>	---
1"	1-30/64"	1-34/64"	<b>GF36P1</b>	---
	1-35/64"	1-38/64"	<b>GF36P2</b>	---
	1-39/64"	1-42/64"	<b>GF36P3</b>	---
1½"	1-20/64"	2"	<b>GF61P1</b>	<b>RGF61P1</b>
	2-1/64"	2-8/64"	<b>GF61P2</b>	<b>RGF61P2</b>
	2-9/64"	2-16/64"	<b>GF61P3</b>	---
2"	2-36/64"	2-40/64"	<b>GF81P1</b>	<b>RGF81P1</b>
	2-41/64"	2-48/64"	<b>GF81P2</b>	<b>RGF81P2</b>
	2-49/64"	2-56/64"	<b>GF81P3</b>	---
3"	3-26/64"	3-40/64"	<b>GF111P1</b>	---
	3-41/64"	3-48/64"	<b>GF111P2</b>	---
	3-49/64"	3-56/64"	<b>GF111P3</b>	---

## Boss Adapters

These fittings have male or female NPT threads and are designed to fit the standard ground joint spuds on page 93. *Supplied with a wing nut, as shown.* For safety tags and safety tape, see page 921.

### Feature:

- plated steel and / or iron

### male NPT adapters



Size	Part #	Pkg Qty
¾"	<b>GMAS6</b>	25
1"	<b>GMAS11</b>	25
1¼"	<b>GMAS16</b>	10
1½"	<b>GMAS21</b>	10
2"	<b>GMAS26</b> <sup>1</sup>	10

<sup>1</sup> uses a special wing nut, part # B27-3

### female NPT adapters



Size	Part #
¾"	<b>GFAS6</b>
1"	<b>GFAS11</b>
1¼"	<b>GFAS16</b>
1½"	<b>GFAS21</b> <sup>1</sup>
2"	<b>GFAS26</b>

<sup>1</sup> Part is produced as a welded fabrication.

## Boss Wing Nut Caps

### Features:

- plated steel and / or iron
- Supplied with 12" chain and washer.
- For best results, use with washer style spuds and washers on pages 95-96.

*Boss wing nut caps are not intended for pressure applications.*



Size	Part #	Opt Qty
¾" and 1"	<b>B12SC</b>	25
1¼" and 1½"	<b>B17SC</b>	25
2"	<b>B27SC</b>	10
3"	<b>B37SC</b>	5